

Whiting Aluminium Dry Freight Door Model: C4 Lite



Roller Shutter Truck Doors

The Whiting C4 Lite is a lightweight yet robust dry freight shutter door, offering a quiet and smooth operation with many benefits.

Features

- Integrated extruded continuous aluminium hinge configuration has been tested beyond 90,000 cycles, equal to 10 years life in normal operation
- Bolt on roller retainers for easy change of rollers to minimise downtime and maintenance costs
- One man can easily assemble/disassemble panels using clip together continuous hinge design
- Independent twin stainless steel cables fitted to every shutter door (Lloyds certified)
- Twin spring balancer provides added reliability and independent lifting capabilities for each individual cable
- Nominal 50mm diameter nylon rollers provides a quieter operation and longer life (twice the life of a 25mm diameter roller)
- Approximately 15% lighter than similar aluminium continuous hinge wooden doors
- Extruded 18mm thick aluminium panels with a centrally located reinforcement rib - 18mm thick for maximum strength and resistance to internal impact
- Spring loaded lock catch provides consistent lock tension and maximum security
- Long-life and durable side, top and bottom seals
- Noise reducing Zytel roller holders and adjustable top closure brackets for easy installation and better top sealing
- Track fixing holes pre-punched
- Extruded aluminium panels are polyester powder coated white RAL 9010 on the outside (natural aluminium on the inside) standard
- Fully recyclable panels

Questions? Call Southern States Group for more information.





Southern States Group reserves the right to modify, without notice, the technical and aesthetic characteristics of the product.





AUSTRALIA

Whiting Aluminium Dry Freight Door Model: C4 Lite



Features



Dual spring balancer for added reliability and independent cable tension.



Stainless steel anti-lozenge brackets with removable Zytel toller retainer allowing easy roller change without removing hinge.



Zytel adjustable top closure bracket for quieter operation and easy set-up.



Heavy duty aluminium bottom seal carrier with easy change four lip seal giving improved performance



Large 50mm diameter sealed nylon rollers for smooth quiet operation and long life.



Continuous hinge technology provides easier and quicker installation.



No.77 spring tension loaded lock complete with keeper for maximum security.

Options

Electrolift powered operation available

Questions? Call Southern States Group for more information.

Southern States Group reserves the right to modify, without notice, the technical and aesthetic characteristics of the product.

